**C**SHARE

## Skid-Steer Loaders / S570 Skid-Steer Loader

# **Specifications & Options**

■ Standard ✓ Optional MA Not Applicable Units US

#### **Bobcat S570**

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	61 hp
Turbocharged Engine	<b>▽</b>

#### **Performance**

Rated Operating Capacity (SAE)	1,950 lb
Tipping Load	3900 lb
Operating Weight	6480 lb
Travel Speed	7.4 mph
Travel Speed (2-speed option)	11 mph

## **Capacities**

Fuel Tank	24.8 gal
-----------	----------

# **Hydraulic System**

System Relief @ Quick Couplers	3,500 psi
Auxiliary Std Flow	17.1 gal/min
Auxiliary High Flow	26.7 gal/min

### **Dimension**

Length	133 in
Length without Attachment	104.6 in
Length with Standard Bucket	133 in
Width	64.7 in
Width (with bucket)	68 in
Height	77.8 in
Height with Operator Cab	77.8 in
Height to Bucket Hinge Pin	119 in
Reach @ Maximum Height	32.6 in
Turning Radius	79.7 in
Wheelbase	42.6 in

#### **Features**

Joystick Control	lacksquare
Air Conditioning	▼
Adjustable Seat	
Backup Alarm	
BICS System (Interlock)	•
Cab Enclosure	<b>✓</b>
Sound Option	
Cab Heater	<b>✓</b>
Operating Lights	•
Parking Brake	
Radio	
Rear Window	
Top Window	
Lift-Arm Support	
Seat Belt	
Suspension Seat	
Two Speed Travel	ightharpoons
Deluxe Instrumentation	✓
Engine Shutdown	
Hydraulic Bucket Positioning	✓
High Flow Option	<b>▽</b>
Auxiliary Hydraulics	•
Spark Arrestor Muffler	•
Bob-Tach Attachment System	•
Power Bob-Tach	<b>▽</b>
ACS (Switchable Controls)	<b>✓</b>
Ride Control	<b>✓</b>
Rear Hydraulics	<b>✓</b>
Horn	

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.